



Marathon Farm Duty

marathonTM
Motors

FARM DUTY / CHORE MOTORS

HIGH AND EXTRA-HIGH TORQUE

Features:

- Ball Bearing
- 1.15 Service Factor
- Totally Enclosed and full gasketed construction for dirty environments
- Shaft Slinger
- UL Recognized and CSA Certified



Single Phase, Totally Enclosed (TEFC), Fan Cooled, Rigid Base									C-Face Kits
HP	RPM	Volts	Frame	Overload Protection	Shaft Diameter	Full Load Amps	Catalogue No.	Notes	Catalogue No.
1/3	1800	115/208-230	56C	manual	5/8"	6.6 / 3.1-3.3	F131	2	Included
1/2	1800	115/208-230	56C	manual	5/8"	8.8 / 4.2-4.4	F132	2	Included
3/4	1800	115/208-230	56C	manual	5/8"	11.0 / 5.4-5.5	F133	2	Included
1	1800	115/208-230	56C	manual	5/8"	13.4 / 6.8-6.7	F134	2	Included
1.5	1800	115/208-230	56HC	manual	5/8"	15.2 / 8.2-7.6	F135	1, 5	Included
2	1800	115/230	145T	manual	7/8"	18.8 / 9.4	Z128	1	A438
	1800	115/230	56HC	manual	5/8"	18.8 / 9.4	K319	1, 5	Included
3	1800	230	184T	manual	1-1/8"	17,0	Z120A-M	2	A666/175691.00
5	1800	230	184T	manual	1-1/8"	20,2	Z121A-M	d, 1	A666/175691.00
	1800	230	215T	manual	1-3/8"	30,0	Z122-M	1	A609
7-1/2	1800	230	215TZ	manual	1-1/8"	32,0	Z115-M	1, X	N/A
	1800	230	215TZ	manual	1-1/8"	32,0	Z115-OLD	1, X	N/A
10	1800	230	215T	manual	1-3/8"	40,0	Z116-M	1, 17, X	A609
	1800	230	215T	manual	1-3/8"	40,0	Z116-OLD	1, 17, X	A609

1 - Capacitor Start / Capacitor Run design for reduced amperage

2 - Capacitor Start Induction Run design

5 - 56H, 145T Combination Base with 12 mounting holes

17 - 1.0 Service Factor

X - 300% and greater starting torque

ES - Energy Saver Design